

VERTICAL

TRADITION Range – Solid bamboo flooring in 3 crossed layers

F15VCC150
F15VCN150
F15VOC150

- Dimensions:** 15 x 150 x 1940 mm
- Coating:** Factory applied UV-varnish layer - matt appearance
Factory applied WOCA oil layer - matt appearance
- Colors:** Caramel and Naturel
- Chamfer:** GO2
- Installation:** Glued: Yes
Floating: No
Floorheating and cooling vloer: Yes if glued
Use in bathroom: Yes if glued and varnished coating
- Wearing surface:** 5 mm
- Box :** Content: 8 planks/box (2,33 m²)
Weight: 25.15 kg
- Maintenance :** cfr maintenance instructions

BRINELL HARDNESS	43 N/mm ² - EN 1534 norm (Report CTIB 5229/2)
CONTRACTION COEFFICIENT	0,14% per % humidity variation
HUMIDITY DEGREE	10% at 20 °C and 65% relative humidity 8% at 20 °C and 50% relative humidity
DENSITY	740 kg/m ³
FIRE NORM	CFLS1 if glued
FORMALDEHYDE EMISSION	0,04 mg/ m ² h - EN 717-2 norm (Report CTIB 5229/2)
THERMISCHE WEERSTAND	0,072 m ² ·K/W - EN 12664 norm (Report CTIB 5229/2)
PCP CONTENT	Below detection limit (Report CTIB 5229/2)
VOC FREE	Below detection limit – EN 15052 norm

Do not forget the accessories!

